

# BATTLE AX® - 10 SERIES

## EXCAVATOR MULCHING HEAD

**LOFTNESS**   
AN EMPLOYEE-OWNED COMPANY



## FEATURES

### Forestry Mulching Heads for **7,000-10,000 lb Excavators**

- “Battle Ax” Rotor Design - Uses Built-In “Depth Gauges” to Control Cutting Depth, Like “Raker” Teeth on a Chainsaw
- **Two-Stage Cutting Chamber** - 2 Shear Bars, Producing a Finer Mulch With Fewer Passes
- **Three Tooth Designs** - 4 Point Beaver Teeth, Quadco Reversible Planer Knives or Double Carbide Teeth
- 45cc Fixed Displacement Gear Motor
- 2 Band Belt Drive
- Efficient Staggered/Spiral Tooth Pattern
- Premium Strength Steel Housing
- **Adjustable Primary Shear Bar**
- Power Requirement - 20-70 Hydraulic HP (15-35.9 GPM @ up to 4100 PSI)
- Optional Spade Hook
- Optional Mounts - Pin-On or Pin Grabber
- 13.5 in (34 cm) Diameter Rotor
- 1 3/4 in (44.5 mm) Piloted Double Taper Roller Bearings
- Machined Anti-Wrap Bearing Protection
- Rotor Speed 1750-2300 RPM
- Steel Deflector Chains
- Case Drain Highly Recommended

**(800)828-7624 / (320)848-6266**

**LOFTNESS.COM**

**BUILD  
& PRICE**

650 Main Street South | Hector, MN 55342



<b>SPECS</b>	Width of Cut in Inches	<b>25</b>
	Recommended Excavator Weight Range (in Pounds)	7K-10K
	Overall Width in Inches	45
	Number of Teeth	16
	Weight Without Mount (in Pounds)	620
	Hydraulic Horsepower Range (Hydraulic HP = GPM X PSI/1714)	20-70
	Hydraulic Flow Range (GPM)	15-35.9

<b>GROUP</b>		Circle/select 1 item from each group in the proper size/model column and product code column. →	<b>PRODUCT CODE</b>	<b>25</b>
<b>1</b>	<b>Size</b>			
	25 Inches		<b>25BX10</b>	\$17,874
<b>2</b>	<b>Teeth</b>			
	Quadco 4 Point Beaver Teeth		<b>Q</b>	\$390
	Quadco Reversible Planer Teeth		<b>P</b>	\$460
	Double Carbide Teeth		<b>S</b>	\$1180
<b>3</b>	<b>Hydraulic Motor</b>			
	Gear Motor - 45cc 15-35.9 GPM up to 4100 PSI (Use with or without Case Drain*)		<b>65</b>	Included
<b>4</b>	<b>Belt Drive Combination</b>			
	15-19.9 GPM		<b>A</b>	Included
	20-23.9 GPM		<b>B</b>	Included
	24-27.9 GPM		<b>C</b>	Included
	28-31.9 GPM		<b>D</b>	Included
	32-35.9 GPM		<b>E</b>	Included
<b>OPT</b>	<b>OPTIONS</b>			
	Spade Hook		<b>H</b>	\$190
<b>5</b>	<b>Mount</b>			
	Common Factory/OEM Specific Mount			\$1,800
	Custom Mount, Pin-On Style (Pins Included) (Not Compatible with Thumb Mounted on Main Pin.)			\$1,800
	Custom Mount, Pin Grabber Style (Welded Pins)			\$1,250
	Special Aftermarket Mount (Call for Pricing and Availability)			CALL

<b>PRODUCT CODE</b>		»		»		»		»		»		»	
	<b>GROUP</b>	1	2	3	4	OPTIONS	5						

\$
<b>TOTAL LIST PRICE</b>

NOTE: **Hoses and Couplers from Power Unit to Head Are NOT Included.**

\*It is highly recommended that you use a Case Drain line, If available. Always set auxiliary hydraulic circuit to "One Way / Continuous Flow" mode. If your power unit does not have that mode available, you will need to add a case drain line.

