BATTLE AX® - 40 SERIES EXCAVATOR MULCHING HEAD

AN EMPLOYEE-OWNED COMPANY

LOFTNES





FEATURES

Forestry Mulching Heads for 36,000-60,000 lb Excavators

- "Battle Ax" Rotor Design Uses Built-In "Depth Gauges" to Control Cutting Depth, Like "Raker" Teeth on a Chainsaw
- Two-Stage Cutting Chamber 2 Shear Bars, Producing a Finer Mulch With Fewer Passes
- Three Tooth Designs Reversible Planer, Hard Surface Planer or Double Carbide
- 135cc Adjustable Displacement Piston Motor
- Efficient Staggered/Spiral Tooth Pattern
- Premium Strength Steel Housing
- Adjustable Primary Shear Bar
- Steel Deflector Chains

- Power Requirement 80-210 Hydraulic HP (25-75 GPM @ up to 6000 PSI)
- 17 in (43.2 cm) Diameter Rotor
- 2 1/2 in (63.5 mm) Piloted Double Taper Roller Bearings
- Machined Anti-Wrap Bearing Protection
- 68 mm Synchronous Belt
- Rotor Speed 1800-2500 RPM
- Optional Spade Hook
- Optional Mounts Pin-On or Pin Grabber
- Optional Tilt Hitch Allows Battle Ax to Be Tilted up to 45 Degrees to the Left or Right (Requires Auxiliary Hydraulic Circuit)





2024 RETAIL PRICING

BATTLE AX® - 40 SERIES

| SPECS | Width of Cut in Inches | 51 |
|-------|--|---------|
| | Recommended Excavator Weight Range (in Pounds) | 36K-60K |
| | Overall Width in Inches | 80.6 |
| | Number of Teeth | 26 |
| | Weight Without Mount in Pounds | 3,010 |
| | Hydraulic Horsepower Range (Hydraulic HP = GPM X PSI/1714) | 80-210 |
| | Hydraulic Flow Range (GPM) | 25-75 |

| GROUP | Circle/select 1 item from each group in the proper size/model column and product code column. ——> | PRODUCT CODE | 51 |
|---------|---|-----------------|----------|
| 1 | Size | | |
| 1 | 51 Inches Standard-Duty | 51BX40 | \$55,173 |
| | Teeth | | |
| 2 | Quadco Reversible Planer Teeth - N49366 (\$41.00 ea.) | Q | \$1,070 |
| 2 | Hard-surfaced Quadco Knives - 203014 (\$61.00 ea.) | Н | \$1,590 |
| | Double Carbide - N49090 (\$75.00 ea.) | S | \$1,950 |
| 3 | Hydraulic Motor | | |
| J | Piston Motor - 135cc 25-75 GPM up to 6000 PSI (Case Drain Required) | 51 | Included |
| 4 | Belt Drive Combination | | |
| | 25-75 GPM | Α | Included |
| OPTIONS | Spade Hook | н | \$530 |
| 9 | Mount | | \$550 |
| | Common Factory/OEM Specific Mount | | \$3,450 |
| | Custom Mount, Pin-On Style (Pins Included) (Not Compatible with Thumb Mounted on Main Pin.) | | \$3,450 |
| | Custom Mount, Pin Grabber Style (Welded Pins) | | \$2,600 |
| 5 | Tilt Hitch with Common Factory/OEM Specific Mount | | \$5,500 |
| | Tilt Hitch with Custom Mount, Pin-On Style (Pins Included) (Not Compatible with Thumb Mounted on Main Pin) (Requires AUX Connection) | | \$5,500 |
| | Tilt Hitch with Custom Mount, Pin Grabber Style (Welded Pins) (Requires AUX Connection.) | | \$4,850 |
| | Special Aftermarket Mount (Call for Pricing and Availability) | | CALL |



(800)828-7624 / (320)848-6266



USD - FOB Factory - Uncrated - Prices Effective 3/14/24 (Subject to Change) 650 Main Street South | Hector, MN 55342