BATTLE AX® - L SERIES skid steer mulching head



restry Mulching Heads for LOW_ELOW Skid Steers (up to 10.3

- Forestry Mulching Heads for LOW-FLOW Skid Steers (up to 10,300 lbs)
 - "Battle Ax" Rotor Design Uses Built-In
 "Depth Gauges" to Control Cutting Depth, Like "Raker" Teeth on a Chainsaw
- **Two-Stage Cutting Chamber** 2 Shear Bars, Producing a Finer Mulch With Less Passes
- Three Tooth Designs 4 Point Beaver Teeth, Quadco Reversible Planer Knives or Double Carbide Teeth
- Fixed Disp. High Pressure Gear-Type Motor
- GPM Rating 15-35.9 GPM up to 4,100 PSI
- Efficient Staggered/Spiral Tooth Pattern
- Premium Strength Steel Housing

- Adjustable Primary Shear Bar
- 13.5 Inch Diameter Rotor
- 1-3/4" Piloted Double Taper Roller Bearings
- Machined Bearing Anti-Wrap
- Rotor Speed 1750-2275 RPM
- 3 Groove Banded V-Belt Drive
- On-Board PSI Gauge to Monitor Capacity
- Steel Deflector Chains
- Universal Skid-Steer Mount
- Increased Visibility
- Hoses Are Included (No Couplers)
- With Case Drain





2024 RETAIL PRICING

| | Width of Cut in Inches | | | | | | |
|-------|-------------------------------|-------|--|--|--|--|--|
| SPECS | Overall Width in Inches | 76 | | | | | |
| | Number of Teeth | | | | | | |
| | Weight in Pounds | 1,728 | | | | | |
| | Hydraulic Horsepower Required | 30-70 | | | | | |

| GROUP | Circle/select 1 item from each group in the proper size/model column and product code column. | PRODUCT CODE | 61 | | | | | |
|-------|---|-----------------|----------|--|--|--|--|--|
| | Size | | | | | | | |
| 1 | 61 Inches | 61BSL | \$24,853 | | | | | |
| | Teeth | | | | | | | |
| 2 | Quadco 4 Point Beaver Teeth - N156042 (\$21.00 ea.) | Q | \$800 | | | | | |
| 2 | Quadco Reversible Planer Teeth - 202970 (\$27.00 ea.) | Р | \$1,030 | | | | | |
| | Double Carbide Teeth - 209036 (\$65.00 ea.) | S | \$2,470 | | | | | |
| 3 | Hydraulic Motor | | | | | | | |
| | High Pressure Gear Motor 45 CC (Use with Case Drain) | 60 | N/C | | | | | |
| | Sheave Combination | | | | | | | |
| | 15-19.9 GPM up to 4,100 PSI | F | \$0 | | | | | |
| 4 | 20-23.9 GPM up to 4,100 PSI | G | \$0 | | | | | |
| 4 | 24-27.9 GPM up to 4,100 PSI | Н | \$0 | | | | | |
| | 28-31.9 GPM up to 4,100 PSI | I | \$0 | | | | | |
| | 32-35.9 GPM up to 4,100 PSI | J | \$0 | | | | | |
| | Options | | | | | | | |
| | Right Hand Hose Kit/PN 208093 | R | \$490 | | | | | |

| PRODUCT CODE | | 》 | | 》 | | 》 | | » | \$ |
|-----------------|---|----------|---|----------|---|----------|---|---------|------------------|
| GROUP | 1 | | 2 | | 3 | | 4 | OPTIONS | TOTAL LIST PRICE |

NOTE: Generic hoses are included. Couplers are NOT included.

Related Auxiliary Hydraulic Oil Cooler, Skid Steer Mounted, Heavy-Duty 140,000 BTU Cooler With Dual Fans For Heavy-Duty Applications - Ask for the "Cool Flow" Cooler From Loftness

(800)828-7624 / (320)848-6266



USD - FOB Factory - Uncrated - Prices Effective 1/1/24 (Subject to Change) 650 Main Street South I Hector, MN 55342