BATTLE AX® - 10 SERIES EXCAVATOR MULCHING HEAD







FEATURES

Forestry Mulching Heads for 7,000-10,000 lb Excavators

- "Battle Ax" Rotor Design Uses Built-In "Depth Gauges" to Control Cutting Depth, Like "Raker" Teeth on a Chainsaw
- Two-Stage Cutting Chamber 2 Shear Bars, Producing a Finer Mulch With Fewer Passes
- Three Tooth Designs 4 Point Beaver Teeth, Quadco Reversible Planer Knives or Double Carbide Teeth
- 45cc Fixed Displacement Gear Motor
- 2 Band Belt Drive
- Efficient Staggered/Spiral Tooth Pattern
- Premium Strength Steel Housing

- Adjustable Primary Shear Bar
- Power Requirement 20-70 Hydraulic HP (15-19.9 GPM @ up to 4100 PSI)
- Optional Spade Hook
- Optional Mounts Pin-On or Pin Grabber
- 13.5 in (34 cm) Diameter Rotor
- 1 3/4 in (44.5 mm) Piloted Double Taper Roller Bearings
- Machined Anti-Wrap Bearing Protection
- Rotor Speed 1750-2300 RPM
- Steel Deflector Chains
- Case Drain Highly Recommended

BUILD

BATTLE AX® - 10 SERIES

SPECS	Width of Cut in Inches	25
	Recommended Excavator Weight Range (in Pounds)	7K-10K
	Overall Width in Inches	45
	Number of Teeth	16
	Weight Without Mount (in Pounds)	620
	Hydraulic Horsepower Range (Hydraulic HP = GPM X PSI/1714)	20-70
	Hydraulic Flow Range (GPM)	15-19.9

GROUP		Circle/select 1 item from each group in the proper ize/model column and product code column.	PRODUCT CODE	25							
	Size										
1	25 Inches		25BX10	\$17,874							
2	Teeth										
	Quadco 4 Point Beaver Teeth		Q	\$390							
	Quadco Reversible Planer Teeth		Р	\$460							
	Double Carbide Teeth		s	\$1180							
2	Hydraulic Motor										
3	Gear Motor - 45cc 15-19.9 GPM up to 4100 F	SI (Use with or without Case Drain*)	65	Included							
4	Belt Drive Combination										
4	15-19.9 GPM		A	Included							
OPTIONS	OPTIONS										
OPTI	Spade Hook		н	\$190							
	Mount										
5	Common Factory/OEM Specific Mount			\$1,800							
	Custom Mount, Pin-On Style (Pins Included (Not Compatible with Thumb Mounted on M			\$1,800							
	Custom Mount, Pin Grabber Style (Welded	Pins)		\$1,250							
	Special Aftermarket Mount (Call for Pricing	and Availability)		CALL							

PRODUCT CODE)		}		} }		}		}		
GROUP	1		2		3		4		OPTIONS		5	П



NOTE: Hoses and Couplers from Power Unit to Head Are NOT Included.

*It is highly recommended that you use a Case Drain line, If available. Always set auxiliary hydraulic circuit to "One Way / Continuous Flow" mode. If your power unit does not have that mode available, you will need to add a case drain line.

(800)828-7624 / (320)848-6266

LOFTNESS.COM

