BATTLE AX® - 20 SERIES







FEATURES

Forestry Mulching Heads for 10,000-20,000 lb Excavators

- "Battle Ax" Rotor Design Uses Built-In "Depth Gauges" to Control Cutting Depth, Like "Raker"
 Teeth on a Chainsaw
- Two-Stage Cutting Chamber 2 Shear Bars,
 Producing a Finer Mulch With Fewer Passes
- Three Tooth Designs 4 Point Beaver Teeth,
 Quadco Reversible Planer Knives or Double
 Carbide Teeth
- 45cc Fixed Displacement Gear Motor
- 3 Band Belt Drive
- Efficient Staggered/Spiral Tooth Pattern
- Premium Strength Steel Housing
- Adjustable Primary Shear Bar

- Power Requirement 20-70 Hydraulic HP (15-35.9 GPM @ up to 4100 PSI)
- Optional Spade Hook With Optional Hydraulic Thumb
- Optional Mounts Pin-On, Pin Grabber or Blank Plate
- 13.5 in (34 cm) Diameter Rotor
- 1 3/4 in (44.5 mm) Piloted Double Taper Roller Bearings
- Machined Anti-Wrap Bearing Protection
- Rotor Speed 1700-2300 RPM
- Steel Deflector Chains
- Case Drain Highly Recommended
- Optional Tilt Hitch Allows Battle Ax to Be Tilted up to 45 Degrees to the Left or Right (Requires Auxiliary Hydraulic Circuit)

(800)828-7624 / (320)848-6266


LOFTNESS.COM



2025 RETAIL PRICING

BATTLE AX® - 20 SERIES

	Width of Cut in Inches		31	41	51
SPECS	Recommended Excavator Weight Range (in Pounds)		10K-15K	15K-20K	15K-20K
	Overall Width in Inches		46.25	56.25	66.25
	Number of Teeth		20	26	32
	Weight Without Mount in Pounds		879	1,084	1,218
	Hydraulic Horsepower Range (Hydraulic HP = GPM X PSI/1714)		20-70	25-70	25-70
	Hydraulic Flow Range (GPM)		15-35.9	15-35.9	15-35.9
GROUP	Circle/select 1 item from each group in the proper size/model column and product code column. —▶	PRODUCT CODE	31	41	51
	Size				
1	31 Inches	31BX20	\$20,983		
	41 Inches	41BX20		\$22,273	
	51 Inches	51BX20			\$23,323
	Teeth				
2	Quadco 4 Point Beaver Teeth - N156042 (\$21.00 ea.)	Q	\$420	\$550	\$670
	Quadco Reversible Planer Teeth - 202970 (\$27.00 ea.)	Р	\$540	\$700	\$860
	Double Carbide Teeth - 209036 (\$65.00 ea.)	S	\$1,300	\$1,690	\$2,080
3	Hydraulic Motor				
J	Gear Motor - 45cc 15-35.9 GPM up to 4100 PSI (Use with or without Case Drain*)	54	Included	Included	Included
	Belt Drive Combination				
4	15-19.9 GPM	Α	Included	Included	Included
	20-23.9 GPM	В	Included	Included	Included
	24-27.9 GPM	С	Included	Included	Included
	28-31.9 GPM	D	Included	Included	Included
	32-35.9 GPM	E	Included	Included	Included
SNO	Special Healt	Н	\$190	\$190	\$190
OPTIONS	Spade Hook Thumb Attachment (Paguirea Spade Hook and ALIX Connection)	T		,	·
0	Thumb Attachment (Requires Spade Hook and AUX Connection) Mount		\$1,030	\$1,030	\$1,030
5	Blank Plate Mount	N49170	\$290	\$290	\$290
		1149170			· ·
	Common Factory/OEM Specific Mount Custom Mount, Pin-On Style (Pins Included)		\$2,200	\$2,200	\$2,200
	(Not Compatible with Thumb Mounted on Main Pin.)		\$2,200	\$2,200	\$2,200
	Custom Mount, Pin Grabber Style (Welded Pins)		\$1,550	\$1,550	\$1,550
	Tilt Hitch with Common Factory/OEM Specific Mount		\$4,400	\$4,400	\$4,400
	Tilt Hitch with Custom Mount, Pin-On Style (Pins Included) (Not Compatible with Thumb Mounted on Main Pin) (Requires AUX Connection)		\$4,400	\$4,400	\$4,400
	Tilt Hitch with Custom Mount, Pin Grabber Style (Welded Pins) (Requires AUX Connection.)		\$3,750	\$3,750	\$3,750
	Special Aftermarket Mount (Call for Pricing and Availability)		CALL	CALL	CALL



\$
TOTAL LIST PRICE

NOTE: Hoses and Couplers from Power Unit to Head Are NOT Included.

*It is highly recommended that you use a Case Drain line, If available. Always set auxiliary hydraulic circuit to "One Way / Continuous Flow" mode. If your power unit does not have that mode available, you will need to add a case drain line.

(800)828-7624 / (320)848-6266

LOFTNESS.COM

