BATTLE AX® - 50 SERIES

LOFTNESS
AN EMPLOYEE-OWNED COMPANY







FEATURES

Forestry Mulching Heads for 50,000-88,000 lb Excavators

- "Battle Ax" Rotor Design Uses Built-In "Depth Gauges" to Control Cutting Depth, Like "Raker"
 Teeth on a Chainsaw
- Two-Stage Cutting Chamber 2 Shear Bars,
 Producing a Finer Mulch With Fewer Passes
- Triple Carbide Teeth
- 165cc Adjustable Displacement Piston Motor
- Efficient Staggered/Spiral Tooth Pattern
- Premium Strength Steel Housing
- Adjustable Primary Shear Bar

- 68 mm Synchronous Belt
- Power Requirement 100-350 Hydraulic HP
 (35-105 GPM @ up to 6000 PSI)
- Optional Mounts Pin-On, Pin Grabber or Blank Plate
- Optional Spade Hook
- 21 in (53.3 cm) Diameter Rotor
- 3 in (76.2 mm) Piloted Double Taper Roller Bearings
- Machined Anti-Wrap Bearing Protection
- Rotor Speed 1700-1900 RPM
- Steel Deflector Chains




2025 RETAIL PRICING

BATTLE AX® - 50 SERIES

SPECS	Width of Cut in Inches	51
	Recommended Excavator Weight Range (in Pounds)	50K-88K
	Overall Width in Inches	85.5
	Number of Teeth	20
	Weight Without Mount in Pounds	4,200
	Hydraulic Horsepower Range (Hydraulic HP = GPM X PSI/1714)	100-350
	Hydraulic Flow Range (GPM)	35-105

GROUP		Circle/select 1 item from each group in the proper size/model column and product code column.	PRODUCT CODE	51	
1	Size				
	51 Inches Standard-Duty		51BX50	\$68,283	
2	Teeth				
	3 Carbide Tooth - 200279 (\$140 ea.)	S	\$2,800	
3	Hydraulic Motor				
	Piston Motor - 165cc 35-105 GPM up	to 6000 PSI (Case Drain Required)	47	Included	
4	Belt Drive Combination				
	35-105 GPM		В	Included	
OPTIONS					
	Spade Hook		Н	\$630	
	Mount				
	Blank Plate Mount		207503	\$600	
	Common Factory/OEM Specific Mou	nt		\$3,450	
5	Custom Mount, Pin-On Style (Pins In (Not Compatible with Thumb Mounte			\$3,450	
	Custom Mount, Pin Grabber Style (W	/elded Pins)		\$2,600	
	Special Aftermarket Mount (Call for F	Pricing and Availability)		CALL	





(800)828-7624 / (320)848-6266

LOFTNESS.COM

