## FLAIL MOWERS

SKID STEER STANDARD OR HIGH-FLOW HYDRAULIC




# FEATURES

### Flail Mowers for Skid Steers

- High Pressure Gear-Type Motor (With or Without Case Drain)
- 15-43 GPM up to 4200 PSI (With Case Drain)
- 15-32 GPM up to 3500 PSI (Without Case Drain)
- Two Knife Designs Flail or Duckfoot
- Toolless Knife Change
- Heavy-Duty Bearing Block
- 3-Groove Banded Belt
- 1-7" Cutting Height
- 1/4" End Plates
- 5 1/2" OD x 3/8" Wall Roller Tube

- 1 1/2" Bearing on Gauge Roller
- Added Gauge Roller Bearing Protection
- 1500-2050 RPM Rotor Speed
- Premium Strength Steel Housing
- Full-Width Gauge Roller with Roller Scraper
- 1 3/4" Rotor Bearings
- Anti-Wrap Bearing Protection
- Hoses Are Included (Couplers Are Not)
- Optional Floating Hitch with Gauge Wheels





#### 2025 RETAIL PRICING

#### FLAIL MOWERS FOR SKID STEERS

SPECS	Width of Cut in Inches	72	90
	Overall Width in Inches	83	101
	Number of Knives (Flail / Duckfoot)	96 / 48	120 / 60
	Weight Without Floating Hitch (in Pounds)	1,360	1,570
	Max Hydraulic Pressure (PSI) - High Pressure Gear Motor Without Case Drain	3,500	3,500
	Max Hydraulic Pressure (PSI) - High Pressure Gear Motor With Case Drain	4,200	4,200
	Max Hydraulic HP Input (Hydraulic Horsepower = GPM x PSI / 1714)	90	90

GROUP	Circle/select 1 item from each group in the proper size/model column and product code column.	PRODUCT CODE	72	90				
	Size							
1	72 Inches	72HM	\$10,944					
	90 Inches	90HM		\$11,794				
	Knife							
2	Duckfoot	D	\$0	\$0				
	Flail	F	\$0	\$0				
	Hydraulic System							
3	Gear Motor - No Case Drain* (15-32.9 GPM) (3500 PSI max)	61	\$4,020	\$4,020				
	Gear Motor - With Case Drain** (15-43.9 GPM) (4200 PSI max)	62	\$3,130	\$3,130				
	Auxiliary Hydraulic Flow (GPM)							
	15-20.9 GPM	Α	\$0	N/A				
4	21-27.9 GPM	В	\$0	\$0				
-	28-32.9 GPM	С	\$0	\$0				
	33-36.9 GPM (Requires Hydraulic System Code "62")	D	\$0	\$0				
	37-43.9 GPM (Requires Hydraulic System Code "62")	E	\$0	\$0				
SNO								
OPTIONS	Floating Hitch with Gauge Wheels	F	\$3780	\$3780				

PRODUCT CODE		»	<b>》</b>	))		»	\$
GROUP	1	2		3	4	OPTIONS	TOTAL LIST PRICE

NOTE: Hoses are included. Couplers are NOT included. \*Hoses: 3/4" #12 MORB - Male O-ring, NO Case Drain Line Required \*\*Hoses: 3/4" #12 MORB - Male O-ring, Case Drain Line (required) : 1/2" - #8MORB

**Related** Auxiliary Hydraulic Oil Cooler, Skid Steer Mounted, Heavy-Duty 140,000 BTU Cooler With Dual Fans For Heavy-Duty Applications - Ask for the "Cool Flow" Cooler From Loftness

#### (800)828-7624 / (320)848-6266



USD - FOB Factory - Uncrated - Prices Effective 1/3/25 (Subject to Change) 650 Main Street South I Hector, MN 55342